PART 0 A/E INSTRUCTIONS

0.01 DESIGN REQUIREMENTS

A. MOUNTING HEIGHTS

1. Refer to the mounting heights schedule in the Drawings section of the DPS Standards for the appropriate mounting heights of equipment.
2. Where ADA requirements conflict with published DPS Standards, use DPS Accessibility Standards.

B. All equipment provided for toilet accessories should be of high durability and vandal-resistant. .

C. Anchorage

1. Coordinate blocking requirements for toilet accessories.
2. Tamper-proof mountings are required
3. At phenolic and solid color reinforced composite (SCRC) toilet partitions, toilet accessories shall be through-bolted.

D. Architect shall confirm wall depths to ensure recessed accessories will fit wall cavity.

E. Architect shall confirm and correctly detail fire rated walls where recessed accessories are to be located.

F. Wall-mounted waste receptacles are prohibited. DPS will provide waste receptacles under separate contract.

G. Provide sanitary napkin disposal units at restrooms used by Middle School students, High School students, and adults.

H. Consider provision of sanitary napkin dispensers at restrooms used by Middle School students, High School students, and adults. Confirm with the DPS Project Manager whether or not coin operation is to be specified.

I. Provide minimum one mirror in each restroom.

G. Architect shall review all locations for the installation of accessories, and should verify that items are shown on Drawings and/or included in this Section. Normal distribution of equipment is as follows.

1. Paper towel holders
   a) One (1) or two (2) per wash fountain.
   b) One (1) per classroom sink.
   c) One (1) per lavatory or pair of lavatories, depending upon layout.
2. Toilet paper holders: one (1) per water closet.
3. Soap dispensers
   a) One (1) per hand wash sink in kitchens.
   b) One (1) per pair of lavatories
   c) One (1) or two (2) per wash fountain, depending upon layout.

PART 1 GENERAL No standards

PART 2 PRODUCTS

2.01 MANUFACTURERS

A. Provide toilet accessories as manufactured by one of the following:

1. Bobrick Washroom Equipment, Inc.
2. Bradley
3. Charles Parker Co.

4. Watrous, Inc.
5. Accessory Specialties, Inc.
6. Kimberly Clark
7. GO-JO

2.02 MATERIALS

1. Stainless steel shall be AISI Type 302/304, 22-gauge (minimum) with a #4 polished finish.
2. Sheet steel: cold-rolled, 20-gauge (minimum).
3. Mounting devices and fasteners
4. Exposed fasteners shall be chrome-plated or stainless steel and shall be theft-resistant.
5. Concealed fasteners shall be of same material as accessory or of galvanized steel.

2.03 PREFERRED EQUIPMENT

A. Toilet paper dispensers: Obtain current specification from DPS Project Manager

B. Paper towel dispensers: Obtain current specification from DPS Project Manager

C. Soap dispensers: Obtain current specification from DPS Project Manager

PART 3 EXECUTION

3.01 INSTALLATION

A. Coordinate installation with the work of other trades, obtaining exact sink, lavatory, urinal and toilet locations from plumbing installers

B. Coordinate type of toilet partition utilized.

END OF SECTION 10800